



75161592

IP20

B.IQ push-button 1gang comfort KNX - Berker B.IQ, glass black

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	1gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
Number of buttons	1

- activation of second user level via object
- one push-button operation for switching, pushing, shutters and dimming

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display no

Materials

Colour of design line	glass black
Colour	black
RAL colour	RAL 9005 - Jet black
Material	glass
Surface appearance	glossy
Type of surface treatment	Painted

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88.5 mm

LED control

LED	with blue operation LED and 2 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



Settings	
Supported configuration modes	system, PB
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
for the stellar to the steel of several control of the second	
 for installation in single standard wall boxes for additional products to complement the installation in matching color platform S.1/B.x for glass frames in the same "style" for additional applications, see the 	_
 for additional products to complement the installation in matching cold platform S.1/B.x for glass frames in the same "style" for additional applications, see the Equipment	Design line B.7
 for additional products to complement the installation in matching color platform S.1/B.x for glass frames in the same "style" for additional applications, see the Equipment Number of actuation points	Design line B.7
 for additional products to complement the installation in matching cold platform S.1/B.x for glass frames in the same "style" for additional applications, see the Equipment	Design line B.7
 for additional products to complement the installation in matching color platform S.1/B.x for glass frames in the same "style" for additional applications, see the Equipment Number of actuation points With anti-theft/dismantling protection	Design line B.7 2 yes
 for additional products to complement the installation in matching color platform S.1/B.x for glass frames in the same "style" for additional applications, see the Equipment Number of actuation points With anti-theft/dismantling protection Product type:	Design line B.7 2 yes

Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ

with dismantling protectionalarm telegram after disconnection from bus coupling unit 1 bit or 1 byte