

	B.IQ push-button 3gang comfort KNX - Berker B.IQ, polar white matt	
	Technical features	
	Architecture	
	Fixing mode	flush-mounting
	Technical version	3gang
	Functions	
5163599	With room temperature controller	no
IP20	- for switch, push-button, dimmer and shutter functions	
	Compatibility	
	- extension unit for light scene push-button	
	Controls and indicators	
	With LED indication	yes
	Number of buttons - activation of second user level via object - one push-button operation for switching, pushing, shutters and dimming	3
	Measurement	
	- value transmitter for dimming, position, brightness and temperature values 1 and 2 b	yte
	Screen	
	With display	no
	Materials	

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt
Type of surface treatment	untreated

2	
Height	88,5 mm
Width	88,5 mm

LED control		
LED	with blue operation LED and 6 white status LEI	
	(labelling field illumination)	

- for bus coupling unit flush-mounted

Connection



Settings	
Supported configuration modes	system, PB
- single and two push-button operation parameterisable	
O Chillians	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
 for installation in single standard wall boxes for additional products to complement the installation in matchir platform S.1/B.x for plastic frames in the same "style" for additional applications, 	
Equipment	
Number of actuation points	6
With anti-theft/dismantling protection	yes
Type of configuration	Laserdruck
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
 with dismantling protection alarm telegram after disconnection from bus coupling unit 1 bit of 	or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ